

# COMPONENT SELECTION GUIDE

## GEN X

Wi-Fi APP Based Controller

Part # - **GEN X**  
Includes Mobile APP

1 - Per RTU or Split System  
Supports 2 - 20 Fully Modulating Zones

Add Part # **GEN X-RM** to expand your GEN X system by adding a GEN X-RM controller for each additional zoned unit.  
(Each GEN X-RM supports 2-20 fully modulating Zones or thermostats)

Daisy Chain: Zonex communications wire and 24VAC from Damper to Damper with wireless stats or Stat to Stat with wired stats 1-24VAC / 100VA Transformer Powers the GEN X and All the Dampers in the System

Each GEN X-RM expansion controller requires an additional transformer to support up to 20 dampers per GEN X-RM

### Color Touch Screen Thermostat

Part # - **EzTouchX**

1- Thermostat per Damper  
Slave Up to 3 Zone Dampers per Stat

### Modulating Zone Dampers

Part # -

**STMPD** + Damper Size - Round Dampers (up to 1.75 S.P)  
**STCD** + Damper Size - Rectangular Dampers (up to 1.75 S.P)

### Color Touch Screen Thermostat to Control Standalone Units

Part # - **SATouchX**

Controls and Networks Standalone RTU or Split systems  
with SA/RA/RH reporting from the mobile app

### Electronic By-Pass Damper

Part #

**STBP** + Damper Size Round By-Pass Dampers  
**STCDBP** + Damper Size Rectangular By-Pass Dampers  
(Includes Integrated Static Pressure Control)  
1-24VAC / 40VA Transformer to Power By-Pass Damper

### RLYX

Part # - **RLYX**

Control and Schedule up to 5 Generic Loads

**THIS COMPLETES YOUR GEN X SYSTEM**

For assistance, contact Zonex at (800) 228-2966  
or visit [zonexproducts.com](http://zonexproducts.com) for more information

