

LD05763

CPS120-024-100U

The UL Listed CPS120-024-100U Power Supply is a sturdy compact and complete 24 Vac power source designed for inclusion in a complete control panel unit. The 96VA unit provides simple power connections and has an illuminated control switch on the 24V output, which is fitted with a protective circuit breaker. The unit also provides a convenient unswitched 120V power point and is installation ready.



- FEATURES**
- UL Recognized to meet code requirements
 - 96VA load capacity
 - Output On/Off control switch
 - Breaker protected 24 Vac Output
 - Simple power connections
 - Useful 120 Vac convenience outlet
 - Installation ready

SPECIFICATIONS

Input:	120 Vac, 60 Hz, 6 Amp max (1 Amp max used by 24V supply)
Output:	24 Vac, 60 Hz, 4 Amp max continuous 120 Vac, 60 Hz, 5 Amp max at convenience outlet (unswitched)
Protective Device:	24 Vac supply with 4 Amp resettable thermal circuit breaker 120 Vac supply, none
Controls:	Double pole switch with power indicating lamp, fitted on the primary of the 24V transformer. 120V convenience outlet power uncontrolled
Connections:	One 5 position terminal block with combination head screws and wire clamps. Provided connection for 120 Vac input, 24 Vac output and safety ground
Housing:	Single piece steel frame
Dimensions:	4-3/4" H x 5" W x 3-3/8" D
Operating Temp:	-15°F to 140°F (-25°C to 60°C)
Weight:	3.75 lbs (1.7 kg)
Standard Accessories:	Instruction / Installation sheet, Warranty Card
Safety Approvals:	UL Recognized for the US and Canada, UL File # E207801