

STAINLESS STEEL WORK STATION

Application

Designed to house a computer, keyboard, monitor and other additional computer equipment in an industrial environment and provide degree of protection from dust, oil and moisture. Stainless steel work stations resist corrosion. For installation information, consult our Installation Manual at www.saginawcontrol.com.

Enclosure Product Code S3

Catalog No.	Height (A)	Width (B)	Depth (C)	Top Size (D)	Industry Standard
SCE-642424SSWS	64.00	24.25	24.25	22.15	IS1
SCE-642432SSWS	64.00	24.25	32.25	29.90	IS1

Construction

- 0.075" stainless steel Type 304.
- Seams continuously welded and ground smooth.
- Pour in place oil and water resistant gasket.
- Flange trough collar around all sides of door opening.
- Concealed hinges.
- Removable doors.
- Ground studs on door and body.
- Large polycarbonate viewing window in top door.
- Lifting eyes for easy handling.
- Rubber pads with provision for leveling pads on bottom of enclosure.
- Black quarter turn latches on top door.
- Black quarter turn wing knob latches on keyboard door.
- Black 3-point flush swing handle in lower front and back doors.
- Gland plate on lower back of enclosure.
- Pullout keyboard shelf with attached self storing mouse shelf and mouse pad.
- Mounting channels welded on sides of interior body for mounting optional sub-panels, racks, mounting angles and shelves.

Notes

Optional sub-panels and accessories available, see pages 236-242

Options

- Optional tamper-resistant inserts or padlocking handles are available.
- Can be special ordered in Type 316/316L stainless steel.

Finish

#4 brushed finish on all exterior surfaces

IS1 Industry Standards

NEMA Type 12 & Type 13
 UL Listed Type 12
 CSA Type 12
 IEC 60529 IP55

***To maintain Type 3R listing, Drainage is required. Install equally rated drainage device or drill a 1/8 to 1/4 inch hole in the bottom center of the enclosure, approximately 1 inch from the right, and 1 inch from the left for drainage, use listed rain-tight or wet location hubs. Drip shield over the door is recommended for all outdoor applications.

230



STAINLESS STEEL WORK STATION TECHNICAL DATA

