

Stainless Steel Enviroline® Series Free-Standing Single-Door Enclosures

Application -
Designed to house electrical and electronic controls, instruments and components. Provides protection from dust, oil and water. For installation information, consult our Installation Manual at www.saginawcontrol.com. For outdoor application a drip shield is recommended.

Construction -

- 0.104" stainless steel Type 304 & 316/316L.
- Seams continuously welded and ground smooth.
- Oil-resistant gasket.
- Flange tough collar around all sides of door opening.
- Stainless steel concealed hinge.
- Black zinc die cast keylocking/radlocking handle.
- Removable and interchangeable doors.
- Black quarter turn latches as required.
- Removable print pocket.
- Lifting eyes for easy handling.
- Ground studs on door and body.
- Mounting channels welded horizontally on sides of interior body at top, bottom and middle for mounting optional panels or rack mounting angles.
- No door stiffeners required.


Finish -

#4 brushed finish on all exterior surfaces. Optional sub-panels are powder coated white.

Accessories - See pages 116-123

- ISS - Industry Standards -**
 NEMA Type 3R, 4, 4X, 12 & Type 13
 UL Listed Type 3R, 4, 4X & 12
 CSA Type 4, 4X & 12
 IEC 60529 IP66

**Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. See the Special Instructions on the Industry Standards page in the Technical Information Section.



Available within 10 working days if not in stock

Back to SS Free Standing Enclosures


Phone (989) 799-6871
 Fax (989) 799-4524



Phone (989) 799-6871
 Fax (989) 799-4524

STAINLESS STEEL ENVIROLINE® SERIES FREE-STANDING SINGLE-DOOR SINGLE-ACCESS ENCLOSURES

TECHNICAL DATA



LATCH NOTE: LATCH TOP AND BOTTOM OF DOOR WHEN DOOR WIDTH IS > 30.00 (762)

