

Heavy Duty Free-Standing Stainless Steel Enclosures For Flange-Mounted Disconnects

Application -
Designed to house electrical equipment and provide protection from dirt, dust, oil and water and to house most standard type disconnects. For installation information, consult our Installation Manual at www.saginawcontrol.com.

Construction -

- 0.104" stainless steel Type 304.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Body stiffeners in large enclosures for extra rigidity.
- Heavy duty lifting eyes anchor into reinforced top.
- Stainless steel concealed hinges.
- Black zinc die cast coniproof/padlocking handle.
- 3-point latching mechanism.
- Black quarter turn latches as required.
- Panel supports.
- Large removable print pockets.
- Oil-resistant gasket.
- Removable sub-panels mount on collar studs.
- Defeater on master door requires a screwdriver to open.
- Ground stud on door.

Disconnect switch (or circuit breaker) and operating mechanism are not furnished with enclosure.

Finish -

#4 brushed finish on all exterior surfaces. Sub-panels are powder coated white.

ISS - Industry Standards -

- NEMA Type 4, 4X, 12 & Type 13
- UL Listed Type 4, 4X & 12
- CSA Type 4, 4X & 12
- IEC 60529 IP66



**Sub-panel included with enclosure. Replacement panels can be ordered. Prices found in the accessory section.


Back to
SS Free-Standing
Enclosures

Phone (989) 799-6871
Fax (989) 799-4524
SCE
SAGINAW
CONTROL &
ENGINEERING
Your Enclosure Source™

HEAVY DUTY FREE-STANDING ENCLOSURES FOR FLANGE-MOUNTED DISCONNECTS TWO-DOOR STAINLESS STEEL ENCLOSURES

Catalog No.	ENCLOSURE PRODUCT CODE S2				SUB-PANEL (P3)			List Price
	Height (A)	Width (B)	Depth (C)	Industry Standard	Height (D)	Width (E)	Panel Price	
SCE-72XM18518SS	72.00	53.75	18.00	ISS 9.890.44	SCE-64P52**	60.00	48.00	Included
SCE-72XM18618SS	72.00	65.75	18.00	ISS 11,145.52	SCE-64P64**	60.00	60.00	Included
SCE-72XM18718SS	72.00	77.75	18.00	ISS 12,965.34	SCE-64P76**	60.00	72.00	Included
SCE-72XM1824SS	72.00	77.75	24.00	ISS 13,286.12	SCE-64P76**	60.00	72.00	Included
SCE-84XM1818SS	84.00	77.75	18.00	ISS 13,758.93	SCE-76P76**	72.00	72.00	Included
SCE-84XM1824SS	84.00	77.75	24.00	ISS 13,930.86	SCE-76P76**	72.00	72.00	Included
SCE-90XM1818SS	90.00	77.75	18.00	ISS 14,691.64	SCE-82P76**	78.00	72.00	Included
SCE-90XM1820SS	90.00	77.75	20.00	ISS 14,777.60	SCE-82P76**	78.00	72.00	Included
SCE-90XM1824SS	90.00	77.75	24.00	ISS 15,418.09	SCE-82P76**	78.00	72.00	Included

Available within 10 working days if not in stock



**Sub-panel included with enclosure. Replacement panels can be ordered. Prices found in the accessory section.

Phone (989) 799-6871
Fax (989) 799-4524
SCE
SAGINAW
CONTROL &
ENGINEERING
Your Enclosure Source™

Heavy Duty Free-Standing Stainless Steel Enclosures For Flange-Mounted Disconnects

Application -
Designed to house electrical equipment and provide protection from dirt, dust, oil and water and to house most standard type disconnects. For installation information, consult our Installation Manual at www.saginawcontrol.com.

Construction -

- 0.104" stainless steel Type 304.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Body stiffeners in large enclosures for extra rigidity.
- Heavy duty lifting eyes anchor into reinforced top.
- Removable center posts permit easy sub-panel installation.
- Stainless steel concealed hinges.
- Black zinc die cast coniproof/padlocking handle on main door with black zinc die cast padlocking handle on slave doors.
- 3-point latching mechanism.
- Black quarter turn latches as required.
- Panel supports.
- Large removable print pockets.
- Oil-resistant gasket.
- Removable sub-panels mount on collar studs.
- Master door is far right-hand door on all enclosures.
- Defeater on master door requires a screwdriver to open.
- Mechanical interlock activated by master door prevents slave doors from being opened first. Doors can be closed in any order.
- Ground stud on door.

Disconnect switch (or circuit breaker) and operating mechanism are not furnished with enclosure.

Finish -

#4 brushed finish on all exterior surfaces. Sub-panels are powder coated white.

ISS - Industry Standards -

- NEMA Type 4, 4X, 12 & Type 13
- UL Listed Type 4, 4X & 12
- CSA Type 4, 4X & 12
- IEC 60529 IP66