

VA-3100 Series Electric Valve Actuators

VA-3100 Series Electric Valve Actuators use a synchronous motor to accurately position Johnson Controls VG2000 Series Cast Iron Flanged Globe Valves in HVAC and industrial applications. These non-spring return electric actuators provide a 675 lb (3,000 N) force output for on/off (floating) or proportional control. Integral auxiliary switches are available for indicating end stop position or for performing switching functions. Position feedback is also available through an isolated 2,000 ohm potentiometer. All models feature a hand crank for manual positioning of the valve, independent of a power supply.



**Figure 1: VA-3100 Series
Electric Valve Actuator**

Features and Benefits	
<input type="checkbox"/> Synchronous Motor with Pressure Switches	Provides a constant running speed and establishes fixed closeoff forces
<input type="checkbox"/> Two-Bolt Coupler Clamp	Provides quick and easy coupling of the actuator to the valve stem
<input type="checkbox"/> On/Off (Floating) or Proportional Control	Allows optimal choice of control signal
<input type="checkbox"/> Adjustable Starting Point, Span, and Action (Proportional Control Model Only)	Provides application flexibility and allows for easy sequencing from only one output signal
<input type="checkbox"/> 0 to 10 VDC Position Feedback Signal (Proportional Control Model Only)	Indicates accurate valve position in response to an input signal up to 10 VDC
<input type="checkbox"/> Auxiliary Switches and Feedback Potentiometer Available on Select Models	Provides independent verification of actuator position
<input type="checkbox"/> Manual Hand Crank	Allows for manual positioning of the valve, independent of a power supply

Table 1: Ordering Data

Actuator Model	Description					
	On/Off (Floating) Control	Proportiona I Control	Feedback		Stem and Valve Size	
			2,000 ohm Potentiometer	Two Auxiliary Switches	“M” Stem (3/8 in.), 2-1/2 through 4 in. Valves	“N” Stem (1/2 in.), 5 and 6 in. Valves
VA-3100-AGA	X	---	---	---	X	X
VA-3100-AGC	X	---	X	X	X	X
VA-3100-HGC	---	X	---	X	X	X

Table 2: Accessories (Order Separately)

Code Number	Shipping Weight lb*	Description
VA-3100-101	0.1	Auxiliary Switch Cam Adjusting Wrench (Used on VA-3100 Series Electric Actuators – One Wrench is Supplied with Each Actuator)
VA-3100-500	3.0	Mounting Kit for Field Mounting VA-3100 Series Electric Actuators to 2-1/2 through 4 in. VG2000 Series Cast Iron Flanged Globe Valves with 3/8 in. “M” Stem (Kit Includes One Stem Jam Nut, One Yoke Adaptor, One Packing Nut, One 2-1/4 in. Length Stem Adaptor for 2-1/2 in. Valves, and One 2-1/2 in. Length Stem Adaptor for 3 and 4 in. Valves)
VA-3100-501	3.5	Mounting Kit for Field Mounting VA-3100 Series Electric Actuators to 5 and 6 in. VG2000 Series Cast Iron Flanged Globe Valves with 1/2 in. “N” Stem (Kit Includes One Stem Jam Nut, One Yoke Adaptor, One Packing Nut, and One Stem Adaptor)
M9000-200	5.7	Commissioning Tool

* lb x 0.454 = kg

Product Guidelines

Before mounting the VA-3100 Series Electric Valve Actuator to a VG2000 Series Cast Iron Flanged Globe Valve, please note the following:

- Mount the valve in an upright position in a conveniently accessible location. When mounted horizontally, orient the yoke so that the yoke supports are positioned vertically, one above the other (as illustrated in Figure 2).




Figure 2: Proper Yoke Orientation

- Protect the actuator from dripping water that could enter the actuator housing and damage the mechanism or motor.
- Do not cover the actuator with insulating material.
- Allow sufficient clearance to remove the actuator (as illustrated in Figure 3).
- Pipe the valve with the flow in the direction of the arrow on the valve body, so that the plug seats against the flow.



CAUTION: Risk of Equipment Damage.

Disconnect all power supplies before making wiring connections or prior to performing maintenance. Check all wiring connections before applying power to the system. Short-circuited or improperly connected wires will result in permanent damage to the equipment.




Figure 3: VA-3100 Series Electric Valve Actuator Dimensions, in. (mm)




Figure 4: VA-3100-AGx Wiring Diagram for On/Off (Floating) Control




Figure 5: VA-3100-HGC Wiring Diagram for Proportional Control

Technical Specifications

Product	VA-3100 Series Electric Valve Actuators	
Force Output	675 lb (3,000 N)	
Power Requirements	On/Off (Floating) Control Models	20 to 28 VAC, 60 Hz; 16 VA Minimum
	Proportional Control Models	20 to 28 VAC, 60 Hz; 18 VA Minimum
Input Signal	On/Off (Floating) Control Models	20 to 28 VAC, 60 Hz
	Proportional Control Models	0 to 10 VDC
Input Impedance	Proportional Control Models Only	5,600 ohms
Feedback Signal	VA-3100-AGC Only	0 to 2,000 ohms
	VA-3100-HGC Only	Approximately 9 VDC Span (0.5 VDC with Valve Stem Fully Down; 9.5 VDC with Valve Stem Fully Up)
Switch Contact Rating	5 A, 24 VAC	
Maximum Stroke	1-21/32 in. (42 mm)	
Nominal Timing for 1 in. Stroke	92 Seconds	
Ambient Operating Temperature Limits (Limited by the Actuator)	On/Off (Floating) Control Models	14 to 140°F (-10 to 60°C)
	Proportional Control Models	14 to 122°F (-10 to 50°C)
Agency Compliance	UL 873 Listed, File E27734, CCN XAPX; cUL C22.2 No. 24-93 Listed, File E27734, CCN XAPX7	
Enclosure Rating	NEMA 3/3R, IP 54	
Shipping Weight	9.7 lb (4.4 kg)	

The performance specifications are nominal and conform to acceptable industry standards. For application at conditions beyond these specifications, consult the local Johnson Controls office. Johnson Controls, Inc. shall not be liable for damages resulting from misapplication or misuse of its products.



Controls Group
507 E. Michigan Street
P.O. Box 423
Milwaukee, WI 53201

Printed in U.S.A.
www.johnsoncontrols.com