

# M6/8

ABB contact for United States  
of America

## General Information

---

<b>Extended Product Type:</b>	M6/8
<b>Product ID:</b>	1SNA400239R1500
<b>EAN:</b>	3472594002390
<b>Catalog Description:</b>	M6/8 Screw Clamp Terminal Blocks - Feed-through - Black
<b>Long Description:</b>	M6/8 Screw Clamp Terminal Blocks - Feed-through - Black,6mm <sup>2</sup> RatedCrossSection, 8mm Spacing G32, TH 35-7.5, TH 35-15 Rail

---

## Categories

---

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Screw Clamp Terminal Blocks

---

## Ordering

---

<b>EAN:</b>	3472594002390
<b>Minimum Order Quantity:</b>	50 piece
<b>Customs Tariff Number:</b>	85369010

---

## Dimensions

---

<b>Product Net Width:</b>	8 mm
<b>Product Net Height:</b>	44.5 mm
<b>Product Net Length:</b>	40.5 mm
<b>Product Net Depth:</b>	40.5 mm
<b>Product Net Weight:</b>	12.8 g

---

## Container Information

---

<b>Package Level 1 Units:</b>	50 piece
<b>Package Level 1 Width:</b>	81 mm
<b>Package Level 1 Height:</b>	47 mm
<b>Package Level 1 Length:</b>	220 mm
<b>Package Level 1 Gross Weight:</b>	0.64 kg
<b>Package Level 1 EAN:</b>	3472594002390
<b>Package Level 2 Units:</b>	1500 piece
<b>Package Level 2 Width:</b>	300 mm
<b>Package Level 2 Height:</b>	300 mm
<b>Package Level 2 Length:</b>	500 mm
<b>Package Level 2 Gross Weight:</b>	20.000 kg
<b>Package Level 3 Units:</b>	36000 piece
<b>Product Packing Type:</b>	Box

---

## Environmental

---

<b>Ambient Air Temperature:</b>	Operation -55 ... +110 °C Storage -55 ... +110 °C
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment

---

## Technical UL/CSA

---

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V
<b>Connecting Capacity-Main Circuit UL/CSA:</b>	Screw Clamp / Flexible 1x 22 ... 8 AWG Screw Clamp / Rigid 1x 22 ... 8 AWG
<b>Connecting Capacity UL/CSA:</b>	Stranded 8 AWG
<b>Flammability According to UL94:</b>	V0

---

## Additional Information

---

<b>Ambient Temperature:</b>	-5 ... +40 °C
<b>Color:</b>	Black
<b>Connecting Capacity-Main Circuit:</b>	Screw Clamp / Flexible 1x 0.5 ... 6 mm <sup>2</sup> Screw Clamp / Rigid 1x 0.5 ... 10 mm <sup>2</sup> Screw Clamp / With Insulated Ferrule 1x 6 mm <sup>2</sup>
<b>Connection Type:</b>	Screw clamp
<b>Degree of Protection:</b>	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
<b>Dielectric Test Voltage:</b>	2000 V
<b>Function:</b>	Feed-through
<b>Gauge Type:</b>	A5
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Insulation Material:</b>	Polyamide
<b>Mounting on DIN Rail:</b>	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
<b>Number of Levels:</b>	1
<b>Pollution Degree:</b>	3
<b>Product Main Type:</b>	M6/8
<b>Product Name:</b>	Terminal block
<b>Rated Cross-Section:</b>	6 mm <sup>2</sup>
<b>Rated Current (I<sub>n</sub>):</b>	Main Circuit 41 A
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	8000 V
<b>Rated Short-time Withstand Current (I<sub>cw</sub>):</b>	for 1 s 720 A
<b>Rated Voltage (U<sub>r</sub>):</b>	1000 V
<b>Recommended Screw Driver:</b>	4.5 mm
<b>RoHS Date:</b>	20050818
<b>Spacing:</b>	8 mm
<b>Sub-Function:</b>	2 connections
<b>Sub-Function 3:</b>	2 connections
<b>Wire Stripping Length:</b>	12.0 mm

---

## Certificates and Declarations (Document Number)

---

<b>CSA Certificate:</b>	1SND161039A0201
<b>cUL Certificate:</b>	1SND161001A0208
<b>Declaration of Conformity - CE:</b>	1SND225001C1009
<b>EAC Certificate:</b>	1SND161009A1100
<b>RoHS Information:</b>	1SND230023F0206

---

## Classifications

---

**ETIM 4.0:** EC000897 - Feed-through terminal block

**ETIM 5.0:** EC000897 - Feed-through terminal block

**Object Classification Code:** X

---

